# 1.1 SYSTEMS ARCHITECTURE

**CONCISE NOTES** 



# 1.1.1 ARCHITECTURE OF THE CPU

The purpose of a **CPU** is to fetch, decode and execute instructions, it does this by:

### **Fetch**

- Fetching the next instructions from the main memory (RAM)
- Brings the instruction back into the CPU

### Decode

• Checks the instruction and work out what needs to be done

### Execute

- Carries out the instruction
  - performing calculations
  - storing information back into memory

CPU is made up from a number of components:

### ALU - Arithmetic Logic Unit

- add, subtract, repeated addition (multiply), repeated subtraction (division)
- AND, OR, XOR, NOT operations
- binary shift operations

### Control Unit

- co-ordinate the activity of the CPU
- sending out control signals to control/synchronise how data moves around the parts of the CPU and memory
- decoding instructions

### Cache Memory

 Most frequently used instructions are copied here to reduce the time needed to fetch instructions from the RAM

### Registers

• Memory locations within the CPU that hold specific pieces of data temporarily and can be accessed very quickly

CPU architecture describes how the different components in the CPU are laid out and communicate with each other. The Von Neumann architecture describes a computer in which the data and instructions are stored in the same area of memory.

Four important registers in a CPU with **Von Neumann architecture**:

### Memory address register (MAR)

• Stores the address of the data to be fetched from, or the address where the data is to be stored

### Memory data register (MDR)

 Stores the data itself which has been read from main memory or is about to be written to main memory

### **Program Counter**

• Stores the address of the next instruction to be fetched from memory. (Which sends the value to the MAR) This counter increments by 1 in each FDE cycle

### Accumulator

Stores the results of calculations

## 1.1.2 CPU PERFORMANCE

### Clock Speed

- The CPU is constantly fetching and executing instructions and the speed at which it does this is determined by an electronic clock
- Clock speeds are measured in hertz (Hz), and means 'number of times per second'
- CPU's usually work at speeds of up to 4GHz (or 4 billion instructions per second)
- Each 'tick' of the clock represents one step in the FDE cycle.
- The faster the clock speed, the more instructions that can be executed every second meaning the program takes less time to run.

### Cache Size

- Cache memory is located between the main memory and the CPU. It is used to hold data that needs to be accessed very quickly.
- Accessing cache memory is much faster than accessing main memory (RAM)
- The more data that can be stored in cache memory rather than main memory, the faster and more efficient the process.
- Cache memory is very expensive.

### Number of processor cores

- Each core can fetch and execute instructions independently so a multiple core processor can handle several instructions at the same time.
- While these multiple cores can work on separate programs or parts of a program at the same time, this is only possible if the program has been written to take advantage of multiple cores

## 1.1.3 EMBEDDED SYSTEMS

An embedded system is a computer system that has been designed for a dedicated function.

- Embedded systems are often manufactured as a single chip
- The dedicated hardware and software make embedded systems more robust and reliable than general-purpose computers.
- Designed and engineered to perform a limited set of tasks to reduce size and improve performance
- Low power consumption to operate from a small power source.
- Small in size and low cost
- Examples include, washing machines, microwaves, home security systems, telephones, televisions, car engine management systems

# If you found this useful, drop a follow to help me out!

**THANK YOU!** 

GGST